

PROGRAMMABLE TEMPERATURE INDICATOR

DPM 4003



The Model 4003, 4 digit (9999) LED Universal Temperature Indicator / Controller can be applied in any application where temperature needs to be displayed and controlled. This DIN 48x96, high accuracy, high-quality panel meter is designed for accurate measurement & display (in °C, °F or K) of temperature from thermocouples (selectable from the front pushbuttons) of Type J, K, N, R, S, T, W5 and from RTDs such as PT100. Ni100 RTD is available as an option as well as other thermocouple types. The thermocouple and RTD signals are accurately linearised by the internal microprocessor. Options include programmable analogue retransmission, single, dual, three & four alarms, peak hold, RS232/485 output. The retransmission is rangeable from the front pushbuttons. The instrument is designed to comply with European CE standards EN 50081 and EN 50082.

- **FEATURES**
 - DIN 48 x 96 enclosure
 - Touch button programmable
 - Programmable for °C, °F, and K, 4 digit display.
 - Programmable for TC of Type J, K, N, S, R, T, W5.
 - Programmable for RTDs such as PT100.
 - Bright Red LED display (optional green)
 - Low cost - high performance design
 - Retransmission option with programmable zero & span
 - RS232 & RS485 bus communication option.

- **OPTIONS**

3001-P Dual setpoints / alarms (P-MOS solid state)	3009 Parallel BCD output
3001-M Dual setpoints / alarms (electromechanical)	3010 95-265V AC/DC power supply
3002 RS 485 output	3012 Peak hold
3003 0 / 4 - 20 mA retransmission	3013 RS 232 output
3004-P 1 setpoint / alarm (P-MOS solid state)	3017 3 setpoints / alarms
3004-M 1 setpoint / alarm (electromechanical)	3018 4 setpoints / alarms
3006 Isolated input/output (order with 3002/3/7/13)	3019 Green display
3007 5 / 10V retransmission	
3008 Galvanic isolated DC supply (12V / 24V)	

• INPUT RANGES & ELECTRICAL SPECIFICATIONS

The probes are linearised in the following temp. ranges:

Type J : -25°C to +900°C	Accuracy : $\pm 0.3^{\circ}\text{C} \pm 1$ count
Type K : -25°C to +1275°C	Cold junction accuracy : $\pm 0.5^{\circ}\text{C}$ after 30 minutes
Type N : +200°C to +1200°C	Warm up time : 30 minutes
Type S : +625°C to +1750°C	Temperature coeff. : ± 30 ppm / $^{\circ}\text{C}$ typical
Type R : +625°C to +1750°C	Conversion time : 1 second
Type T- : -235°C to +25°C	Operating temperature range : 0 to +50°C
Type T+ : -35.0°C to 330.0°C	Storage temperature range : -40 to +85°C
Type W5 : +1150°C to +2050°C	Data retention : 10 years minimum
PT100 : -165.0°C to +600.0°C (max 999.9°F)	European CE standard : CE to EN50081 & EN50082
Ni100 (option) : -60.0°C to +235.0°C	RF immunity : Self recovery
	Alarms, electromechanical : 250V AC, 30V DC, 2A, PF=1
	Alarms, photomos : 400 V AC/DC, 0.5A, PF=1
	Retransmission accuracy : 0.1% (over full temp. range)

TC resolution : 1°C (Type T+ is 0.1°C)
RTD resolution : 0.1°C

• PROGRAMMABLE SETTINGS

Display : °C, °F, or Kelvin	*Retransmission zero : -1999 to 9999
Broken TC : Selectable high or low	*Retransmission span : -1999 to 9999
Broken RTD : Selectable high or low	*Alarm values : -1999 to 9999
	*Alarm hysteresis : 0 to 9999 (default 1)
Other thermocouples and RTDs are available. Please consult the factory for special requirements.	*Alarm delay : 0 to 255 seconds (default 0)
	*Alarm relay settings : Selectable HIGH or LOW alarm
	*Alarm relay state : Selectable normally open or normally closed
* indicates option	*RS485 address : 1 to 127
	*RS232 / RS485 baud : 2400, 4800, 9600, 19200

NOTE The DPM is normally supplied factory set as per customer's requirements, and does therefore not need programming upon delivery.

• ORDERING EXAMPLE

Option modules (see page 1)

MODEL 4003 - 3001P - 3003
Input : PT100
Aux Supply : 230 VAC
Retransmission : 4 - 20 mA = 0 - 300.0 °C
Setpoints : 2 setpoints with solid state relays

• POWER SUPPLY

115 / 230 VAC $\pm 10\%$ (standard), 3.5VA, 50/60Hz, link selectable
12VDC or 24VDC non-isolated on request, 5VA
12VDC isolated switch mode power supply option (Option 3008-12), 5VA
24VDC isolated switch mode power supply option (Option 3008-24), 5VA
95V-265V AC/DC switch mode power supply option (Option 3010), 5VA

GUARANTEE

This product is guaranteed against faulty workmanship or defective material, for a period of 3 (three) years from date of delivery by INSTROTECH.

INSTROTECH undertakes to replace without charge all defective equipment which is returned to it (transportation costs prepaid) during the period of guarantee, provided there is no evidence that the equipment has been abused or mishandled in any way.

INSTROTECH reserves the right to alter any specification without notice.

DISTRIBUTED BY:

65/119 Belair Road
Torrens Park SA 5062

 **INSTROTECH** PTY LTD
INSTRUMENTATION AND PROCESS CONTROL

email : instrotech@senet.com.au
Tel (08) 8373 5677
Fax +61 8 8373 5667